

# SAFETY DATA SHEET

## Speed-Sew Premium Fabric Glue

Version 1.1      Revision Date: 04/11/2023      SDS Number: F000002688      Date of last issue: 07/01/2016  
Date of first issue: 07/01/2016

---

### SECTION 1. IDENTIFICATION

Product name : Speed-Sew Premium Fabric Glue

Product code : F000002688

#### Manufacturer or supplier's details

Company name of supplier : Canmec Enterprises

Address : PO BOX 30088  
Vancouver, BC , V6P 5A0

Telephone : 1.866.824.8947

Telefax : 1.866.824.8947

Emergency telephone number : 1.866.824.8947 - support@speed-sew.com

---

### SECTION 2. HAZARDS IDENTIFICATION

#### GHS Classification

Not a hazardous substance or mixture.

#### GHS label elements

Not a hazardous substance or mixture.

#### Other hazards

None known.

---

### SECTION 3. COMPOSITION/INFORMATION ON INGREDIENTS

#### Hazardous components

Chemical name	CAS-No.	Concentration (%)
Rubber, natural	9006-04-6	>= 90 - < 100
ethane-1,2-diol	107-21-1	>= 1 - < 5

Actual concentration is withheld as a trade secret

---

### SECTION 4. FIRST AID MEASURES

- If inhaled : Move to fresh air in case of accidental inhalation of vapours.  
Oxygen or artificial respiration if needed.  
Call a physician or poison control centre immediately.  
If symptoms persist, call a physician.
- In case of skin contact : Wash off immediately with soap and plenty of water while removing all contaminated clothes and shoes.  
If symptoms persist, call a physician.
- In case of eye contact : In case of eye contact, remove contact lens and rinse immediately with plenty of water, also under the eyelids, for at least 15 minutes.  
Keep eye wide open while rinsing.  
Remove contact lenses.

# SAFETY DATA SHEET

## Speed-Sew Premium Fabric Glue

Version	Revision Date:	SDS Number:	Date of last issue: 07/01/2016
1.1	04/11/2023	F000002688	Date of first issue: 07/01/2016

---

If swallowed	: Seek medical advice. Do NOT induce vomiting. If symptoms persist, call a physician. If conscious, drink plenty of water. Never give anything by mouth to an unconscious person.
Most important symptoms and effects, both acute and delayed	: None known.

---

### SECTION 5. FIREFIGHTING MEASURES

Suitable extinguishing media	: Foam Carbon dioxide (CO <sub>2</sub> ) ABC powder Water mist
Specific hazards during fire-fighting	: Burning produces irritant fumes. Exposure to decomposition products may be a hazard to health. Cool closed containers exposed to fire with water spray. Do not allow run-off from fire fighting to enter drains or water courses.
Specific extinguishing methods	: Use extinguishing measures that are appropriate to local circumstances and the surrounding environment. Use water spray to cool unopened containers. Fire residues and contaminated fire extinguishing water must be disposed of in accordance with local regulations.
Special protective equipment for firefighters	: In the event of fire, wear self-contained breathing apparatus. Use personal protective equipment. Exposure to decomposition products may be a hazard to health.

---

### SECTION 6. ACCIDENTAL RELEASE MEASURES

Personal precautions, protective equipment and emergency procedures	: Use personal protective equipment. Ensure adequate ventilation. Material can create slippery conditions. Use non-slip safety shoes in areas where spills or leaks can occur.
Environmental precautions	: Prevent further leakage or spillage if safe to do so. Do not let product enter drains. Do not allow contact with soil, surface or ground water. Do not allow uncontrolled discharge of product into the environment.
Methods and materials for containment and cleaning up	: Dam up. Soak up with inert absorbent material (e.g. sand, silica gel, acid binder, universal binder, sawdust). Sweep up and shovel. Pick up and transfer to properly labelled containers. Clean contaminated floors and objects thoroughly while observing environmental regulations.

---

# SAFETY DATA SHEET

## Speed-Sew Premium Fabric Glue

Version 1.1      Revision Date: 04/11/2023      SDS Number: F000002688      Date of last issue: 07/01/2016  
Date of first issue: 07/01/2016

---

### SECTION 7. HANDLING AND STORAGE

- Advice on protection against fire and explosion : Keep away from open flames, hot surfaces and sources of ignition. No special protective measures against fire required.
- Advice on safe handling : Wear personal protective equipment.  
Handle with care.  
Take care to avoid waste and spillage when weighing, loading and mixing the product.
- Conditions for safe storage : No smoking.  
Keep in properly labelled containers.  
Observe label precautions.  
Keep containers tightly closed in a dry, cool and well-ventilated place.
- Materials to avoid : Do not freeze.  
Keep away from food and drink.  
Keep away from tobacco products.
- 

### SECTION 8. EXPOSURE CONTROLS/PERSONAL PROTECTION

#### Components with workplace control parameters

Components	CAS-No.	Value type (Form of exposure)	Control parameters / Permissible concentration	Basis
Rubber, natural	9006-04-6	TWA (Inhalable fraction)	0.0001 mg/m <sup>3</sup> (as inhalable allergenic proteins)	ACGIH
ethane-1,2-diol	107-21-1	C	50 ppm 125 mg/m <sup>3</sup>	OSHA P0

- Engineering measures** : Handle only in a place equipped with local exhaust (or other appropriate exhaust).  
Maintain air concentrations below occupational exposure standards.

#### Personal protective equipment

- Respiratory protection : No personal respiratory protective equipment normally required.  
When workers are facing concentrations above the exposure limit they must use appropriate certified respirators.  
Use NIOSH approved respiratory protection.
- Hand protection  
Material : Impervious gloves
- Eye protection : Safety glasses with side-shields  
Tightly fitting safety goggles  
Face-shield
- Skin and body protection : Chemical resistant apron
-

# SAFETY DATA SHEET

## Speed-Sew Premium Fabric Glue

Version	Revision Date:	SDS Number:	Date of last issue: 07/01/2016
1.1	04/11/2023	F000002688	Date of first issue: 07/01/2016

---

Protective measures	: Footwear protecting against chemicals Skin should be washed after contact. Change working clothes after each workshift. : Avoid contact with skin. When using do not eat, drink or smoke. Personal protective equipment comprising: suitable protective gloves, safety goggles and protective clothing The type of protective equipment must be selected according to the concentration and amount of the dangerous substance at the specific workplace.
Hygiene measures	: Do not smoke. Keep away from food and drink. Avoid contact with skin, eyes and clothing. Change working clothes after each workshift.

---

### SECTION 9. PHYSICAL AND CHEMICAL PROPERTIES

Appearance	: liquid
Colour	: milky, white
Odour	: strong, ammoniacal
pH	: 10.0 - 11.0
Melting point/range	: 0 °C
Boiling point/boiling range	: 100 °C
Flash point	: No data available
Evaporation rate	: 1
Vapour pressure	: 760 mmHg (100 °C)
Relative vapour density	: 0.63
Density	: 0.94 g/cm <sup>3</sup>
Solubility(ies)	
Water solubility	: completely miscible
Solubility in other solvents	: Not applicable
Partition coefficient: n-octanol/water	: No data available
Viscosity	
Viscosity, dynamic	: ca. 3,200 cPs
Explosive properties	: Not applicable

---

### SECTION 10. STABILITY AND REACTIVITY

Reactivity	: Stable
Possibility of hazardous reactions	: Stable under recommended storage conditions.

---

# SAFETY DATA SHEET

## Speed-Sew Premium Fabric Glue

Version	Revision Date:	SDS Number:	Date of last issue: 07/01/2016
1.1	04/11/2023	F000002688	Date of first issue: 07/01/2016

---

Conditions to avoid	: Protect from frost.
Incompatible materials	: Oxidizing agents Strong acids and strong bases
Hazardous decomposition products	: Carbon dioxide (CO <sub>2</sub> ), carbon monoxide (CO), oxides of nitrogen (NO <sub>x</sub> ), dense black smoke.

---

### SECTION 11. TOXICOLOGICAL INFORMATION

#### Acute toxicity

**Product:**

Acute oral toxicity : Remarks: This information is not available.

Acute inhalation toxicity : Remarks: This information is not available.

Acute dermal toxicity : Remarks: This information is not available.

#### Skin corrosion/irritation

**Product:**

Remarks: slight irritation

#### Serious eye damage/eye irritation

**Product:**

Remarks: slight irritation

#### Respiratory or skin sensitisation

**Product:**

Remarks: This information is not available.

#### Carcinogenicity

**IARC**

No component of this product present at levels greater than or equal to 0.1% is identified as probable, possible or confirmed human carcinogen by IARC.

**OSHA**

No component of this product present at levels greater than or equal to 0.1% is on OSHA's list of regulated carcinogens.

**NTP**

No component of this product present at levels greater than or equal to 0.1% is identified as a known or anticipated carcinogen by NTP.

#### Further information

**Product:**

Remarks: Inhalation of vapours may cause irritation of the respiratory system in very susceptible persons.

# SAFETY DATA SHEET

## Speed-Sew Premium Fabric Glue

Version	Revision Date:	SDS Number:	Date of last issue: 07/01/2016
1.1	04/11/2023	F000002688	Date of first issue: 07/01/2016

---

Ingestion causes irritation of upper respiratory system and gastrointestinal disturbance.

---

### SECTION 12. ECOLOGICAL INFORMATION

#### Ecotoxicity

##### Product:

Toxicity to fish :  
Remarks: No data available

Toxicity to daphnia and other aquatic invertebrates :  
Remarks: No data available

Toxicity to algae :  
Remarks: No data available

#### Persistence and degradability

No data available

#### Bioaccumulative potential

No data available

#### Mobility in soil

No data available

#### Other adverse effects

No data available

---

### SECTION 13. DISPOSAL CONSIDERATIONS

#### Disposal methods

Waste from residues : Do not dispose of waste into sewer.  
Dispose of in accordance with local regulations.  
Can be landfilled or incinerated, when in compliance with local regulations.

Contaminated packaging : Clean container with water.  
Empty containers should be taken to an approved waste handling site for recycling or disposal.

---

### SECTION 14. TRANSPORT INFORMATION

#### International Regulations

##### UNRTDG

Not regulated as a dangerous good

##### IATA-DGR

Not regulated as a dangerous good

##### IMDG-Code

# SAFETY DATA SHEET

## Speed-Sew Premium Fabric Glue

Version 1.1      Revision Date: 04/11/2023      SDS Number: F000002688      Date of last issue: 07/01/2016  
Date of first issue: 07/01/2016

---

Not regulated as a dangerous good

**Transport in bulk according to Annex II of MARPOL 73/78 and the IBC Code**

Not applicable for product as supplied.

### National Regulations

#### 49 CFR

Not regulated as a dangerous good

#### 49 CFR

Not regulated as a dangerous good

---

### SECTION 15. REGULATORY INFORMATION

**SARA 302** : This material does not contain any components with a section 302 EHS TPQ.

**SARA 313** : The following components are subject to reporting levels established by SARA Title III, Section 313:

ethane-1,2-diol                      107-21-1

### California Prop 65


WARNING: This product can expose you to chemicals including methanol, which is(are) known to the State of California to cause birth defects or other reproductive harm. For more information, go to [www.P65Warnings.ca.gov](http://www.P65Warnings.ca.gov).

---

### SECTION 16. OTHER INFORMATION

#### Further information

#### NFPA:



#### HMIS III:

<b>HEALTH</b>	<b>2</b>
<b>FLAMMABILITY</b>	<b>1</b>
<b>PHYSICAL HAZARD</b>	

0 = not significant, 1 =Slight,  
2 = Moderate, 3 = High  
4 = Extreme, \* = Chronic

Revision Date : 04/11/2023

---

# SAFETY DATA SHEET

## Speed-Sew Premium Fabric Glue

Version	Revision Date:	SDS Number:	Date of last issue: 07/01/2016
1.1	04/11/2023	F000002688	Date of first issue: 07/01/2016

---

The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process, unless specified in the text.

US / EN